



TEMPERATURE SENSORS

THERMOCOUPLE / RTD

SENSOR TYPE	RANGE (°C)
Themocouple 'K'	0 to 1370
Themocouple 'J'	0 to 760
Themocouple 'R'	0 to 1760
Themocouple 'S'	0 to 1760
Themocouple 'T'	0 to 400
Themocouple 'N'	0 to 1300
Themocouple 'E'	0 to 720
Pt - 100	(-) 200 to 530


Thermocouple : -

Junction : Grounded / Ungrounded
 Sheathing : SS / SS 316 / Inconel
 Diameter : 1 mm / 1.5 mm / 3 mm / 5 mm / 6 mm /
 10 mm OD Mineral Insulated
 Length : 100 mm / 300 mm Standard
 Fitment : Bayonet Fitting / Washer / Grommet Type
 Termination : Bulk Head or Pig Tail
 Extension Cable : Teflon / SS Braided / Fibre Glass

RTD : -

Type : Pt - 100 / Pt - 200 / Pt - 500 / Pt - 1000
 Sheathing : SS / SS 316
 Diameter : 4 mm / 6 mm
 Length : 100 mm / 300 mm Standard
 Fitment : Bayonet Fitting / Washer / Grommet Type
 Termination : Bulk Head or Pig Tail
 Extension Cable : Teflon / SS Braided

Note : Please specify the Type of Thermocouple, Length & Extension Cable along with fitment while ordering.



Manufactured by :

Ajay Sensors & Instruments

45/17, 12th "A" Cross, Gubbanna Indl. Garden,
VI Block, Rajajinagar, Bangalore - 560 010.

Tel : 080 - 2330 4997; Fax : 080 - 2338 1040.

E-mail: ajaysensors@yahoo.com ;

Website: www.ajaysensors.com

Marketed By :

N.B. : Due to continuous development, we reserve the right to amend any Specification without notice.